



US009860415B2

(12) **United States Patent**
Zeng

(10) **Patent No.:** **US 9,860,415 B2**
(45) **Date of Patent:** **Jan. 2, 2018**

(54) **METHOD AND DEVICE FOR
PICTURE-BASED BARCODE ENCODING
AND DECODING**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(71) Applicant: **INSTITUTE FOR INFORMATION
INDUSTRY**, Taipei (TW)

5,243,655 A 9/1993 Wang 380/51
5,726,435 A 3/1998 Hara et al. 235/294
(Continued)

(72) Inventor: **Yi-Chong Zeng**, Keelung (TW)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **INSTITUTE FOR INFORMATION
INDUSTRY**, Taipei (TW)

TW 451590 B 8/2001
TW 200823795 A 6/2008

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 158 days.

OTHER PUBLICATIONS

(21) Appl. No.: **14/945,394**

Xiang Zhou, et al., A Semi-Fragile Watermark Scheme for Image
Authentication, Proceedings of 10th International Multimedia
Modelling Conference, 374-377, Jan. 5-7, 2004.
(Continued)

(22) Filed: **Nov. 18, 2015**

(65) **Prior Publication Data**

US 2017/0076416 A1 Mar. 16, 2017

Primary Examiner — Andrew W Johns

(30) **Foreign Application Priority Data**

(74) *Attorney, Agent, or Firm* — CKC & Partners Co.,
Ltd.

Sep. 16, 2015 (TW) 104130634 A

(57) **ABSTRACT**

(51) **Int. Cl.**

G06T 1/00 (2006.01)
H04N 1/32 (2006.01)
G06K 19/06 (2006.01)

(52) **U.S. Cl.**

CPC ... **H04N 1/32277** (2013.01); **G06K 19/06046**
(2013.01); **G06T 1/0035** (2013.01); **G06T**
2201/0053 (2013.01); **H04N 2201/3236**
(2013.01); **H04N 2201/3269** (2013.01); **H04N**
2201/3284 (2013.01)

(58) **Field of Classification Search**

CPC ... G06T 1/0021; G06T 1/0028; G06T 1/0035;
G06T 1/0092; G06T 2201/0051; G06T
2201/0061; H04N 1/32208; H04N
1/32251; H04N 1/32267; H04N
2201/3269;

A method for picture-based barcode encoding and decoding
is provided herein. The method for picture-based barcode
encoding includes: transforming an original data into an
original data bitstream; performing an error correction on
the original data bitstream for translating the original data
bitstream into an error corrected bitstream; selecting all or
part of the picture as an encoded area; calculating a data
storage capacity of the encoded area; adjusting a size of the
error corrected bitstream or a size of the encoded area for
equalizing a data storage capacity of an encoded data
bitstream and the data storage capacity of the encoded area;
and adjusting a pixel value of the encoded area according to
the encoded data bitstream.

(Continued)

12 Claims, 9 Drawing Sheets

